




# How To Remove Casters from Clorox<sup>®</sup> Total 360<sup>®</sup>



1. Place device on steady, clean, flat surface, remove bottles, turn on power and spray the remaining liquid in the system.



2. Once empty, gently lay the device on its side.



3. Rotate the caster so the metal caster frame is pointed towards the corner of the device. The metal frame is a good location to grab the caster.



4. With one hand holding the device firmly in place, firmly pull on the caster with your other hand. It should pull out with some resistance.



**Optional:** If the caster will not come out by hand, gently pry open with a flat blade screwdriver in between the metal caster dome & the blue plastic device floor. Be gentle in order to not break the plastic.



For more information, contact  
the Clorox Total 360 Support Team.  
U.S.A.: 866-397-8360  
Canada: 877-694-7360  
Service@CloroxTotal360Support.com  
www.CloroxTotal360Support.com

© 2022 Clorox Professional Products Company,  
1221 Broadway, Oakland, CA 94612.


NI-56731




# How To Install Casters on Clorox<sup>®</sup> Total 360<sup>®</sup>



1. Place device on steady flat surface. Ensure there are no bottles and no remaining liquid in the system.



2. Hold the device firmly in place with one hand. With your other hand, insert a caster into the caster mounting hole.



3. Firmly push the caster in. Note the gap between the metal caster bell on the other casters and adjust to be the same distance from the blue floor. If this is the first caster to be installed, make the rest the same distance from the blue floor.



**Note:** After the device is back in service, the casters may settle until they are fully seated.



For more information, contact  
the Clorox Total 360 Support Team.  
U.S.A.: 866-397-8360  
Canada: 877-694-7360  
Service@CloroxTotal360Support.com  
www.CloroxTotal360Support.com

© 2022 Clorox Professional Products Company,  
1221 Broadway, Oakland, CA 94612.

NI-56731